

# NEW CAR DIRECTIONS

**SPEED** Avoid high speeds while the car is new. To obtain best results, IT SHOULD NOT BE DRIVEN FASTER THAN 30 TO 35 MILES PER HOUR FOR THE FIRST 500 MILES.

**OIL** Keep the oil at "F" on the measuring rod, especially during the first few hundred miles. Never let it get below the mark "L." Remove measuring rod and wipe with a dry cloth before testing the level. OIL SHOULD BE CHANGED AFTER THE FIRST 500 MILES AND EVERY 500 MILES THEREAFTER. Summer oil should conform to S.A.E. specification 40, and Winter oil to S.A.E. specification 20.

**BRAKES** this car is equipped with 4-wheel mechanical brakes which are quick and positive in action. Keep the car under control at all times to avoid the necessity for sudden application of brakes which might result in discomfort to passengers or collision from rear.

**FAN BELT** Do not tighten fan belt. The V-type fan belt does not require tight adjustment for proper operation. Too tight an adjustment will result in excessive wear on fan belt and generator bearings, particularly at higher speeds.

**TIRES** For easy riding qualities, proper braking and long life keep the tires, both front and rear, inflated to 35 pounds. (4.75—21 tires should be inflated to 40 pounds).

**INSPECTION** To insure best results have an Authorized FORD DEALER inspect this car and make necessary minor adjustments after the first five hundred miles of running.

**TRIPLEX SAFETY GLASS** <sup>Triplex</sup> <sup>Safety</sup> Glass is used in this car for your protection. Do not replace Triplex Safety Glass with plate glass. If replacement is necessary use TRIPLEX SAFETY GLASS.

---

---

**DRIVE SAFELY**